GSM Construction Chemicals

GAST SUPER EMULSION PAINT

Technical Datasheet

Product Description

GAST SUPER EMULSION PAINT is a versatile, water-based emulsion paint, engineered for both interior and exterior applications. It offers excellent durability and a high-quality finish on a variety of surfaces including wood, wall putty, and gypsum. Formulated to withstand diverse weather conditions, this paint is an ideal choice for projects requiring a resilient and attractive finish.



Recommended Uses

- Final coat applications for both indoor and outdoor environments.
- Applicable on a broad range of surfaces for residential, commercial, and industrial settings.

Features and Benefits

- Versatility: Suitable for interior and exterior use, adaptable to various substrates including wood, concrete, cement, wall putty, and gypsum.
- Weather Resistance: Designed to resist the effects of weather, ensuring longevity and maintaining aesthetic appeal across all seasons.
- Water-Based: Eco-friendly with easier cleanup and lower odor compared to solvent-based paints.
- Durability: Provides a durable coat that resists fading and wear, ideal for high-traffic areas and exterior exposure.

Application Instructions

- Surface Preparation: Ensure the surface is clean, dry, and free from dust, grease, or any loose material. Sanding may be required for smooth substrates or previously painted surfaces.
- Application Method: Can be applied using a brush, roller, or spray equipment. Stir well before use.
- Thinning: If necessary, thin with water up to a maximum of 10% by volume.
- Drying Time: Touch dry in 1-2 hours under normal conditions. Allow 4-6 hours before applying a second coat if necessary.
- Coverage: Typically covers 10-12 m^2 per litre, depending on surface porosity and application method.

GSM Construction Chemicals

GAST SUPER EMULSION PAINT

Technical Datasheet

Storage and Handling

- Store in a cool, dry place away from direct sunlight and extreme temperatures.
- Keep container tightly closed when not in use to prevent drying out.
- Dispose of any waste material in accordance with local environmental regulations.

Safety Precautions

- Use in a well-ventilated area.
- Wear protective gear to avoid skin and eye contact.
- Wash thoroughly with soap and water after handling.

Technical Support

For further information or assistance, please contact GAST Solar Mechanics PLC technical services. Our team is available to provide advice on product selection, application techniques, and safety precautions to ensure optimal results for your project.